

Her daim ingilizce mail atma mail template

\$(Language) sistemden bamsz olarak dorudan en-US set ettiimizde mail dorudan ingilizce olarak deerleri sisteme gönderecektir.

Mail

```
<Script>
  <If>
    <Then>
      <Condition>
        <IsEmpty>
          <Value>$(Originator)</Value>
        </IsEmpty>
      </Condition>
      <Perform>
        <SetVariable Name="$(Originator)">
          <Value>Sistem</Value>
        </SetVariable>
      </Perform>
    </Then>
  </If>
  <If>
    <Then>
      <Condition>
        <IsEmpty>
          <Value>$(Initiator)</Value>
        </IsEmpty>
      </Condition>
      <Perform>
        <SetVariable Name="$(Initiator)">
          <Value>Sistem</Value>
        </SetVariable>
      </Perform>
    </Then>
  </If>

  <SetVariable Name="$(Language)">
    <Value>en-US</Value>
  </SetVariable>

<Transform
  Data="::*"
  ReturnType="OuterXml">
  <StyleSheet>
    <Value
      Culture=""
      Target="None">
      <xsl:stylesheet version="1.0" xmlns:xsl="http://www.w3.org/1999/XSL/Transform">
        <xsl:output method="html" encoding="utf-8" doctype-public="-//W3C//DTD XHTML 1.0 Transitional//EN"
doctype-system="http://www.w3.org/TR/xhtml1/DTD/xhtml1-transitional.dtd" />
        <xsl:param name="EBIFlowWebUrl" />
        <xsl:param name="To" />
        <xsl:param name="WorkItemName" />
        <xsl:param name="WorkItemUrl" />
        <xsl:param name="Initiator" />
        <xsl:param name="Originator" />
        <xsl:param name="Actions" />
        <xsl:param name="Language" />
        <xsl:template match="/">
          <html>
            <head>
              <meta http-equiv="Content-Type" content="text/html; charset=utf-8" />
              <xsl:element name="base">
```

```

    <xsl:attribute name="href">
      <xsl:value-of select="$EBIFlowWebUrl" />
    </xsl:attribute>
  </xsl:element>
</title>EBIFlow</title>
<style>
  BODY { font-family: tahoma;font-size:12px; }
  P { margin:5px; padding-top:10px; }
  TABLE { margin:5px }
  TABLE TD { padding:2px }
  TABLE TH { text-align:left; }
  A { text-decoration:none; }
  A:hover { text-decoration:underline; }
</style>
</head>
<body>
  <xsl:if test="$Language='tr-TR'">
    <p>
      Sayn <xsl:value-of select="$To" />,
    </p>
    <p>
      Adnza gönderilen <strong>
        <xsl:value-of select="$WorkItemName" />
      </strong> isimli i ak admn lütfen deerlendiriniz.
    </p>
    <p>
      <xsl:element name="a">
        <xsl:attribute name="href">
          <xsl:value-of select="$WorkItemUrl" />
        </xsl:attribute>
        Formu açmak için lütfen buraya tklaynz.
      </xsl:element>
    </p>
    <table>
      <tr>
        <th>Balatan</th>
        <td>
          <xsl:value-of select="$Initiator" />
        </td>
      </tr>
      <tr>
        <th>Kimden</th>
        <td>
          <xsl:value-of select="$Originator" />
        </td>
      </tr>
    </table>
    <br/>
    <p>
      <small>
        Bu mesaj <strong>kiiye özel</strong> gönderilmitir. Lütfen paylamaynz.
      </small>
    </p>
  </xsl:if>

  <xsl:if test="$Language='en-GB'">
    <p>
      Mr. / Mrs. <xsl:value-of select="$To" />,
    </p>
    <p>
      Please examine the <strong>
        <xsl:value-of select="$WorkItemName" />
      </strong> process.
    </p>
    <p>
      <xsl:element name="a">
        <xsl:attribute name="href">
          <xsl:value-of select="$WorkItemUrl" />
        </xsl:attribute>
        Click here to open the form.
      </xsl:element>
    </p>
  </xsl:if>

```

```
</p>
<table>
  <tr>
    <th>Initiator</th>
    <td>
      <xsl:value-of select="$Initiator" />
    </td>
  </tr>
  <tr>
    <th>Originator</th>
    <td>
      <xsl:value-of select="$Originator" />
    </td>
  </tr>
</table>
<br/>
<p>
```

forward.

```
  <small>
    This message contains <strong>private and confidential</strong> information. Please do not
  </small>
</p>
</xsl:if>
```

```
<xsl:if test="$Language='en-US'">
  <p>
    Mr. / Mrs. <xsl:value-of select="$To" />,
  </p>
  <p>
    Please examine the <strong>
      <xsl:value-of select="$WorkItemName" />
    </strong> process.
  </p>
  <p>
    <xsl:element name="a">
      <xsl:attribute name="href">
        <xsl:value-of select="$WorkItemUrl" />
      </xsl:attribute>
      Click here to open the form.
    </xsl:element>
  </p>
```

```
<table>
  <tr>
    <th>Initiator</th>
    <td>
      <xsl:value-of select="$Initiator" />
    </td>
  </tr>
  <tr>
    <th>Originator</th>
    <td>
      <xsl:value-of select="$Originator" />
    </td>
  </tr>
</table>
<br/>
<p>
```

forward.

```
  <small>
    This message contains <strong>private and confidential</strong> information. Please do not
  </small>
</p>
</xsl:if>
```

```
<xsl:if test="$Language='de-DE'">
  <p>
    Herr / Frau <xsl:value-of select="$To" />,
  </p>
  <p>
    Bewerten Sie den zugesendeten <strong>
      <xsl:value-of select="$WorkItemName" />
    </strong>
  </p>
```

 genannten Arbeitsablauf.
</p>
<p>
<xsl:element name="a">
 <xsl:attribute name="href">
 <xsl:value-of select="\$WorkItemUrl" />
 </xsl:attribute>
 Klicken Sie hier um die Anfrage zu öffnen.
</xsl:element>

</p>
<table>
 <tr>
 <th>Initiator</th>
 <td>
 <xsl:value-of select="\$Initiator" />
 </td>
 </tr>
 <tr>
 <th>Sender</th>
 <td>
 <xsl:value-of select="\$Originator" />
 </td>
 </tr>
</table>

<p>
 <small>

Diese Nachricht enthält private und vertrauliche Informationen. Bitte nicht weiterleiten.

</small>
</p>
</xsl:if>

<xsl:if test="\$Language='fr-FR'">
<p>
 Monsieur / Madame <xsl:value-of select="\$To" />,
</p>
<p>
 S'il vous plaît évaluer l'étape de flux de travail
 <xsl:value-of select="\$WorkItemName" />
 qui est envoyé à votre nom.
</p>

<p>
<xsl:element name="a">
 <xsl:attribute name="href">
 <xsl:value-of select="\$WorkItemUrl" />
 </xsl:attribute>
 S'il vous plaît cliquer ici pour ouvrir le forme.
</xsl:element>

</p>
<table>
 <tr>
 <th>Initiateur</th>
 <td>
 <xsl:value-of select="\$Initiator" />
 </td>
 </tr>
 <tr>
 <th>Envoyeur</th>
 <td>
 <xsl:value-of select="\$Originator" />
 </td>
 </tr>
</table>

<p>
 <small>

Ce message contient des informations privées et confidentielles.

 Ne pas transmettre.
</small>
</p>

```

</xsl:if>

<xsl:if test="$Language='ru-RU'">
  <p>
    Mr. / Mrs. <xsl:value-of select="$To" />,
  </p>
  <p>
    Please examine the <strong>
      <xsl:value-of select="$WorkItemName" />
    </strong> process.
  </p>
  <p>
    <xsl:element name="a">
      <xsl:attribute name="href">
        <xsl:value-of select="$WorkItemUrl" />
      </xsl:attribute>
      Click here to open the form.
    </xsl:element>
  </p>
  <table>
    <tr>
      <th>Initiator</th>
      <td>
        <xsl:value-of select="$Initiator" />
      </td>
    </tr>
    <tr>
      <th>Originator</th>
      <td>
        <xsl:value-of select="$Originator" />
      </td>
    </tr>
  </table>
  <br/>
  <p>
    <small>
      <strong> </strong> nformation.Please .
    </small>
  </p>
</xsl:if>

<br/>
<br/>
<div style="text-align:right;position:absolute;left:0;top:0;width:100%">
  
</div>
</body>
</html>
</xsl:template>
</xsl:stylesheet>
</Value>
</StyleSheet>
<Arguments>
  <Argument Name="EBIFlowWebUrl">$(EBIFlowWebUrl)</Argument>
  <Argument Name="To">$(To)</Argument>
  <Argument Name="WorkItemName">$(WorkItemName)</Argument>
  <Argument Name="WorkItemUrl">$(WorkItemUrl)</Argument>
  <Argument Name="Initiator">$(Initiator)</Argument>
  <Argument Name="Originator">$(Originator)</Argument>
  <Argument Name="Actions">$(Actions)</Argument>
  <Argument Name="Language">$(Language)</Argument>
</Arguments>
</Transform>
</Script>

```